

-19-

WHAT IS CLAIMED IS

5

1. An apparatus for coding a binary image representing an object shape, comprising:

an inferior symbol detecting unit which decides which one of binary zero and binary one is
10 an inferior symbol that is of smaller occurrence within a given area of the binary image;

a divided portion generating unit which divides a rectangular block of the given area into divided portions;

15 a map information generating unit which generates map information for each one of the divided portions, the map information indicating whether a corresponding one of the divided portions has the inferior symbol included therein; and

20 a coding unit which encodes only the divided portions that have the inferior symbol included therein, wherein an identification of the inferior symbol, the map information, and the encoded divided portions are output from said
25 apparatus.

30

2. The apparatus as claimed in claim 1, wherein the binary zero and the binary one represent an interior of the object shape and an exterior of the object shape.

-20-

3. The apparatus as claimed in claim 1,
wherein said dividing portion generating unit is a
pixel-line generating unit that divides the
rectangular block into the divided portions that are
5 pixel lines.

10 4. The apparatus as claimed in claim 3,
further comprising:

a block generating unit which divides the
given area into rectangular blocks, wherein the
given area is one of macro blocks into which the
15 binary image is divided; and

a block map information generating unit
which generates block map information indicative of
whether a corresponding one of the rectangular
blocks has the inferior pixel included therein,
20 wherein each of the rectangular blocks is divided
into the divided portions by the divided portion
generating unit only if there is the inferior pixel
included therein.

25

5. The apparatus as claimed in claim 3,
further comprising:

30 another inferior symbol detecting unit
which detects another inferior symbol within one of
macro blocks into which the binary image is divided;
a block generating unit which divides the

-21-

one of the macro blocks into rectangular blocks including said rectangular block; and

a block map information generating unit which generates block map information indicative of whether a corresponding one of the rectangular blocks has said another inferior pixel included therein, wherein each of the rectangular blocks is divided into the divided portions by the divided portion generating unit only if there is said another inferior pixel included therein.

6. The apparatus as claimed in claim 5, wherein said given area coincides with said rectangular block.

7. The apparatus as claimed in claim 3, further comprising a pixel rearranging unit which rearranges pixels within the pixel lines before said coding unit encodes the divided portions, wherein information about rearrangement of the pixels is output from said apparatus.

8. The apparatus as claimed in claim 1, wherein said coding unit encodes the map information

-22-

before the map information is output from said apparatus.

5

9. An apparatus for coding a binary image representing an object shape, comprising:

an inferior symbol detecting unit which
10 decides which one of binary zero and binary one is
an inferior symbol that is of smaller occurrence;

a divided portion generating unit which
divides a block of the binary image into divided
portions; and

15 a coding unit which encodes only the
divided portions that have the inferior symbol
included therein.

20

10. A method of coding a binary image representing an object shape, comprising the steps of:

25 deciding which one of binary zero and
binary one is an inferior symbol that is of smaller
occurrence within a given area of the binary image;

dividing a rectangular block of the given
area into divided portions; and

30 encoding only the divided portions that
have the inferior symbol included therein.

